



Matrix Water Well Drill Pipe Data Table

Tool Joint O.D.	Tool Joint I.D.	Midbody O.D.	Tool Joint Connection
A	B	C	D
2.75"	1.50"	2.75"	2.375" Mayhew Jr.
3.00"	1.50"	3.00"	2.375" Mayhew Jr.
3.00"	1.50"	3.00"	2.375" F.E.D.P.
3.25"	1.50"	3.25"	2.375" Mayhew Regular
3.50"	1.75"	3.50"	2.375" Internal Flush
4.00"	1.25"	4.00"	2.875" Regular
4.50"	2.125"	4.50"	2.875" Internal Flush
4.50"	1.50"	4.50"	3.50" Regular
4.625"	2.125"	4.50"	3.5" Full Hole
4.75"	2.688"	4.75"	3.5" Internal Flush
5.00"	2.75"	5.00"	3.50" Internal Flush
5.00"	2.125"	5.00"	3.5" Full Hole
5.00"	1.50"	5.00"	3.5" Regular
5.50"	2.813"	5.50"	4.0" Full Hole
5.50"	2.25"	5.50"	4.5" Regular
6.00"	3.00"	6.00"	4.5" Full Hole
6.00"	2.25"	6.00"	4.5" Regular

Matrix Water Well Drill Rods are available with a variety of midbody wall thicknesses and wrench flat configurations to fit your specific weight and handling requirements.